


Plastic bodied limit switch

Series 188

Article number 6186135553



Electrical Data		
Rated insulation voltage	U _i	250 V AC
Conv. thermal current	I_{the}	10 A
Rated operational voltage	U_{e}	240 V
Utilization category		AC-15, U /l 240 V / 3 A
Direct opening action	\ominus	acc. to IEC/EN 60947-5-1, annex K
Short-circuit protective device		Fuse 10 A gG
Protection class		II (totally insulated)

BERNSTEIN AG . Hans-Bernstein-Straße 1 . 32457 Porta Westfalica . www.bernstein.eu

Technical Data



Mechanical data		
Enclosure	Thermoplastic, glass fibre reinforced (UL 94-V0)	
Cover	Thermoplastic, glass fibre reinforced (UL 94-V0)	
Actuator	Turret head, roller (thermoplastic)	
Ambient air temperature	-30 °C +80 °C	
Contact type	1 NC, 1 NO (Zb)	
Mechanical life	10 x 10 ⁶ operating cycles	
Switching frequency	≤ 100 / min.	
Assembly	2 x M4	
Connection	4 screw connections (M3,5)	
Conductor cross-sections	Solid: 0,5 1,5 mm² or Litz wire with ferrules: 0,5 1,5 mm²	
Cable entrance	1 x Reduction-ring M16 – ½" NPT (thermoplastic)	
Weight	≈ 0,11 kg	
Installation position	operator definable	
Protection type	IP65 acc. to IEC/EN 60529	

Actuation

The actuating device is preferably started from 2 sides.

By loosening the 4 screws the actuation assembly can be rotated in 90 degree increments such that 8 actuation directions are possible.

The actuation assembly is to be again fastened to the housing using the 4 screws.

ID for safety engineering		
B10d	20 x 10 ⁶ switching cycles	

Standards	
VDE	0660 T100, DIN EN 60947-1, IEC 60947-1
VDE	0660 T200, DIN EN 60947-5-1, IEC 60947-5-1
DIN	IN ISO 13849-1

EU Conformity

acc. to directive 2006/95/EC

Approvals

 $_{C}CSA_{US}$ A300 (same polarity)

Notes

The degree of protection specified (IP code) applies only to a properly closed cover and the use of an equivalent cable gland with adequate cable.

Schindler, ID-No.: 188 648

BERNSTEIN AG . Hans-Bernstein-Straße 1 . 32457 Porta Westfalica . www.bernstein.eu