

Technical Data



Inductive Proximity Switch

Series M08

Description **KIB-M08PÖ/1,5-KL5**

Article number **6602701866**

Wiring Diagram



Identifying characteristics in accordance with EN 60947-5-2

Electrical data

Rated operating distance	S_n	1,5mm
Standard target		8 x 8mm, t=1mm; material: FE360
Effective operating distance	S_r	1,4 ... 1,7mm
Assured operating distance	S_a	0 ... 1,2mm
Switching element function		DC, N.C.
Repeat accuracy	R	≤ 5%
Differential travel (hysteresis)	H	≤ 0,2 x S_r
Rated operational voltage	U_e	12 – 24V DC
Operational voltage range	U_B	10 – 36V DC
Rated insulation voltage	U_i	75V DC
Rated impulse withstand voltage	U_{imp}	500V
Voltage drop	U_d	≤ 1,5V (add. 0,06V per m cable and 200mA Load @ 20°C)
Utilization category		DC 13
Rated operational current	I_e	≤ 200mA
Minimum operational current	I_m	≤ 1mA
Off-state current	I_r	< 0,3mA
No-load supply current	I_o	≤ 11mA
Rated conditional short-circuit current		100A
Switching element		Permanent overload and s.c.p.
Short-circuit protection		pulsed
Frequency of operating cycles	f	1000Hz
Rated supply frequency		DC
Mounting		flush
False polarity protection		yes
Time delay before availability	t_v	≤ 50ms

Electromagnetic compatibility (EMC)

Electromagnetic field test	IEC 61000-4-3
Electrostatic discharge test	IEC 61000-4-2
Electrical fast transient immunity test (Burst)	IEC 61000-4-4
Impulse voltage withstand ability (Surge)	IEC 255-5
Radiated disturbance field strength	EN 55011

Mechanical Data

Front cap	PA6.6, black
Enclosure	Stainless steel (Niro 1.4305)
Ambient air temperature	-25°C ... +70°C
Type of protection	IP67
Pollution degree	3 (Pollution of the active zone can cause impairments of the operating distances.)
Indication	LED, yellow
Termination type	Cable 3 x 0,14mm ² , PVC - Outer jacket, high flexible, black

EU Conformity

acc. to Directive 2004 / 108 / EC

This document will not become the contractual basis; the details included herein do not constitute any descriptions of expected conditions, so that warranties/claims for defects on account of possible variations of the actual qualities from the qualities described herein are explicitly excluded. All rights reserved. Specifications subject to change without notice!

Date of issue: 13.10.2011 / Page 1 of 1
Document : 6602701866_en.doc / Last update: 1 / 0477-11