


# Float switch

## Series Standard-Float switch

Description **MAT-733 KSS 0390**

Article number **6835165014**



Electrical data	
Rated voltage	$U_r$ 250 V
max. switching current	0,5 A
max. switching capacity	30 VA
Rated insulation voltage	$U_i$ 300 V AC
Rated impulse withstand voltage	$U_{imp}$ 2,5 kV AC
Overvoltage category	II
Switching element	1 C.O., rising level 2 C.O., falling level
Protection class	I

Mechanical data	
Terminal box material	Aluminium coated RAL 3016
Switching tube material	X6CrNiMoTi17-12-2 (1.4571)
Float material	PP
- density	about 0,62 g/cm <sup>3</sup> ±10 %
- depth of immersion	30 mm ± 2 mm ( to a fluid-density of 1 g/cm <sup>3</sup> )
Adjusting ring material	X6CrNiMoTi17-12-2 (1.4571)
Gasket material	NBR
Ambient air temperature	-5 °C to +100 °C
Liquid temperature	-5 °C to +100 °C
Connection	Connecting block inside the terminal box
Protection type	IP 65 acc to IEC529 / EN 60529
Max. pressure	5 bar

Standards
DIN EN 60947-5-1

EU Conformity
acc. to directive 2014/35/EU (Low-Voltage-Directive)

General details
The measures of the switching points refer to a fluid-density of 1 g/cm <sup>3</sup> . The tolerance of the switching points is ±2 mm Pay attention to the contact protection, when switching inductive or capacitive loads. Maximum data must not be exceeded!

Inductive loads			
<p>Direct current</p> <p>Suppression of voltage peaks with a free-wheeling diode</p>	<p>Alternating voltage</p> <p>Suppression of voltage peaks with a VDR</p>	<p>Suppression of voltage peaks with an RC element</p>	

Capacitive loads and lamp loads		
Contact protection with resistors for limiting current		