


Float switch

Series Standard-Float switch

Description **MAE-741 LHS 0420**Article number **6846191004**

Characteristic features in accordance with EN 60947-5-1

Electrical data	
max. switching voltage	250 V
max. switching current	1,0 A
max. switching capacity	60 VA
min. switching capacity	3 VA
mechanical life	10 ⁷ to 10 ⁹ switches depending on the load
Switching element	O = N.C. rising level m ₂ = N.C. falling level m ₁ = N.C. rising level U = N.C. falling level
Protection class	II (totally insulated)

Mechanical data


Bolting material	X 10 CrNiS 18 9 (1.4305)
Terminal box material	X 6CrNiMoTi 17 12 2 (1.4571)
Switching tube material	X6CrNiMoTi17-12-2 (1.4571)
Float material	X6CrNiMoTi17-12-2 (1.4571)
- density	about 0,65 g/cm ³ ±10 %
- depth of immersion	32 mm ± 2 mm (to a fluid-density of 1 g/cm ³)
Adjusting ring material	X6CrNiMoTi17-12-2 (1.4571)
Ambient air temperature	-5 °C to +60 °C
Liquid temperature	-5 °C to +60 °C
Connection	Cable 10 x 0,5 mm ² x 3 m ± 5 %; PVC; wire No. 9 and GNYE pinched off
Protection type	IP 65 acc to IEC529 / EN 60529
Max. pressure	10 bar

EU Conformity

acc. to directive 2006/95/EC

General details

Repeatability of switching points is ±0,05 mm based on the same geometrical conditions as of a switch device.
 The measures of the switching points refer to a fluid-density of 1 g/cm³.
 The tolerance of the switching points is ±2 mm
 Pay attention to the contact protection, when switching inductive or capacitive loads. Maximum data must not be exceeded!

Inductive loads**Capacitive loads and lamp loads**