


PCB Terminal Block


10.16 mm Pin Spacing

- Board Mount PCB
- 18A Current Rating
- Height 16mm
- Modular
- Double Row Pins



MV25Dxx-10,16-V

Front Wire Entry / Double Pin



Electrical Ratings		UL US E178356		IEC		VDE N.40019705	
Usergroup	B	C	D				
Rated Voltage	300V	-	300V	750V			
Rated Current	18A	-	18A	24A			
Wire Size	<i>solid</i>	30-14 AWG	-	30-14 AWG	0.25mm ² - 4.0mm ²		
	<i>stranded</i>	30-14 AWG	-	30-14 AWG	0.25mm ² - 2.5mm ²		

Ordering Information

No. Poles	Length (mm)	Std. Pack	Order #
2	15.24	100	MVB-252-D
3	25.40	100	MVB-253-D
4	35.56	100	MVB-254-D
5	45.72	100	MVB-255-D
6	55.88	100	MVB-256-D
7	66.04	100	MVB-257-D
8	40.64	100	MVB-258-D
9	45.72	100	MVB-259-D
10	50.80	100	MVB-2510-D
11	55.88	100	MVB-2511-D
12	60.96	100	MVB-2512-D

Material Specifications

Clamp	Nickel-Copper
Solder tab	Tin-Plated Copper
Screw	Galvanized Steel
Insulating Material	Polyamide
Flammability Class	V0 UL94
Operating Temperature	-30°C - +105°C

Installation Data

Screw Size	M3
Torque	0.8Nm (4.5 lb.in.)
Stripping Length	max. 8mm
Clamp Opening	2.8 x 2.8mm
PCB Hole Size	1.3mm

