


PCB Terminal Block


7.50 mm Pin Spacing

- Board Mount PCB
- 20A Current Rating
- Height 11.5mm
- Modular



MVE11xx-7,5-V

Front Wire Entry



Electrical Ratings		UL E178356		IEC	VDE N.40019705
Usergroup	B	C	D		-
Rated Voltage	300V	-	300V		750V
Rated Current	20A	-	20A		24A
Wire Size	<i>solid</i>	30-14 AWG	-	30-14 AWG	0.25mm ² - 2.5mm ²
	<i>stranded</i>	30-14 AWG	-	30-14 AWG	0.25mm ² - 2.5mm ²

Ordering Information

No. Poles	Length (mm)	Std. Pack	Order #
2	15.0	200	MVE112-7,5-V
3	22.5	200	MVE113-7,5-V
4	30.0	100	MVE114-7,5-V
5	37.5	100	MVE115-7,5-V
6	45.0	100	MVE116-7,5-V
7	52.5	100	MVE117-7,5-V
8	60.0	100	MVE118-7,5-V
9	67.5	100	MVE119-7,5-V
10	75.0	100	MVE1110-7,5-V
11	82.5	100	MVE1111-7,5-V
12	90.0	100	MVE1112-7,5-V

Material Specifications

Clamp	Tin-Plated Copper
Solder tab	Tin-Plated Copper
Screw	Galvanized Steel
Insulating Material	Polyamide
Flammability Class	V0 UL94
Operating Temperature	-30°C - +105°C

Installation Data

Screw Size	M2.5
Torque	0.4 Nm (3.6 lb.in.)
Stripping Length	max. 7mm
Clamp Opening	2.6 x 2.4mm
PCB Hole Size	1.5mm

