

SPLICER TERMINAL BLOCKS

- Quick mounting and wiring
- IP20 Finger Safe
- DIN Rail or Panel Mount
- No caps to open or remove
- Material
Housing: Polyamide
Metal Body: Aluminum

38064



38057



38059



Part Number:: **38064** **38057** **38059**

	38064		38057		38059	
	UL File E98082		UL File E98082		UL File E98082	
Current Rating	175A	175A	400A	400A	800A	800a
Voltage Rating	600V AC	690V AC	600V AC	690V AC	600V AC	690V AC
No. of Inputs	1	1	1	2	2	2
Total Wire Range	14-2/0 AWG	2.5mm ² -70mm ²	6 AWG-400kcmil	16mm ² -185mm ²	4 AWG-600kcmil	25mm ² -300mm ²
Screw Type	Hex 5		Hex 10		Hex 10	
No. of Outputs	1	1	1	1	2	2
Total Wire Range	14-2/0 AWG	2.5mm ² -70mm ²	6 AWG-400kcmil	16mm ² -185mm ²	4 AWG-600kcmil	25mm ² -300mm ²
Screw Type	Hex 5		Hex 10		Hex 10	

Torque

Wire Range	14-8 AWG	2.5mm ² -10mm ²	6-3 AWG	16mm ² -25mm ²	4-3 AWG	2	5mm ²
Torque	35 lb-in	3.9 Nm	130 lb-in	14.7 Nm	130 lb-in		14.7 Nm
Wire Range	6-2 AWG	16mm ² -35mm ²	2-1/0 AWG	35mm ² -50mm ²	2-1/0 AWG		35mm ² -50mm ²
Torque	80 lb-in	9.0 Nm	170 lb-in	19.2 Nm	170 lb-in		19.2 Nm
Wire Range	1-2/0 AWG	50mm ² -70mm ²	2/0 AWG-400kcmil	70mm ² -185mm ²	2/0 AWG-400kcmil		70mm ² -185mm ²
Torque	100 lb-in	11.4 Nm	220 lb-in	24.9 Nm	220 lb-in		24.9 Nm
Wire Range	-	-	-	-	500-600kcmil		300mm ² -240mm ²
Torque	-	-	-	-	310 lb-in		35.1 Nm

