



Material:
• Perbanan

Characteristics:
• PG and metric thread

| Temperature Range |
|-----------------------------|
| -25 to 120°C (-13 to 248°F) |

| Connecting thread | | Internal Diameter mm | Thickness mm (d) | Cat. No. | Std. Pk. |
|-------------------|--------|----------------------|------------------|----------|----------|
| PG | metric | | | | |
| PG 7 | M 12 | 10 | 1.5 | 8112070 | 1000 |
| PG 9 | M 16 | 13 | 1.5 | 8112096 | 1000 |
| PG 11 | | 16 | 1.5 | 8112118 | 1000 |
| PG 13.5 | M 20 | 18 | 1.5 | 8112134 | 1000 |
| PG 16 | | 20 | 1.5 | 8112169 | 1000 |
| PG 21 | | 25 | 2 | 8112215 | 1000 |
| | M 25 | 22 | 2 | 8112250 | 100 |
| | M 32 | 28 | 2 | 8112320 | 100 |
| PG 29 | | 33 | 2 | 8112290 | 1000 |
| | M 40 | 37 | 2 | 8112400 | 100 |
| PG 36 | | 43 | 2 | 8112363 | 1000 |
| | M 50 | 48 | 2 | 8112500 | 100 |
| PG 42 | | 50 | 2 | 8112428 | 1000 |
| PG 48 | M 63 | 55 | 2 | 8112630 | 1000 |
| | M 75 | 68 | 2.6 | 8112675 | 100 |



Sealing Ring / Neoprene

Material:
• Neoprene, black

Characteristics:
• PG and metric thread

| Temperature Range |
|-----------------------------|
| -25 to 100°C (-13 to 212°F) |

| Connecting thread | External diameter mm | Internal diameter mm | Thickness mm | Cat. No. | Std. Pk. |
|-------------------|----------------------|----------------------|--------------|----------|----------|
| PG | | | | | |
| PG 7 | 17 | 11.3 | 1.2 | 8113301 | 100 |
| PG 9 | 20 | 13.9 | 1.2 | 8113302 | 100 |
| PG 11 | 23 | 17.1 | 1.2 | 8113303 | 100 |
| PG 13.5 | 25 | 19.0 | 1.2 | 8113304 | 100 |
| PG 16 | 27 | 21.0 | 1.2 | 8113305 | 100 |
| PG 21 | 34 | 26.6 | 1.5 | 8113306 | 50 |
| PG 29 | 45 | 35.2 | 1.5 | 8113307 | 50 |
| PG 36 | 56 | 45.2 | 1.5 | 8113308 | 50 |
| PG 42 | 67 | 52.2 | 1.5 | 8113309 | 50 |
| PG 48 | 72 | 57.7 | 1.5 | 8113310 | 50 |
| Metric | | | | | |
| M 12 | 15 | 10 | 1.2 | 8113490 | 100 |
| M 16 | 20 | 13.9 | 1.2 | 8113302 | 100 |
| M 20 | 24 | 18 | 1.2 | 8113492 | 100 |
| M 25 | 30 | 23 | 1.2 | 8113493 | 100 |
| M 32 | 40 | 30 | 1.5 | 8113494 | 100 |
| M 40 | 48 | 38 | 1.5 | 8113495 | 100 |
| M 50 | 58 | 48 | 1.5 | 8113496 | 100 |
| M 63 | 75 | 61 | 1.5 | 8113497 | 100 |
| M 75 | 90 | 73 | 1.5 | 8113498 | 100 |

