


Ground Spring Clamp

Altech offers 'Screwless' Spring Clamp Ground Terminal Blocks. Specially designed alloy feet helps in achieving very low contact resistance and vibration proof grounding.


CSCG series terminals can be mounted on Din 35 rail along with other terminal blocks of CSC series. The terminal block profile matches with that of CSC terminal block of same wire size.

Special features of CSCG terminal blocks are:


- Vibration proof grounding
- Very low contact resistance because of special alloy feet
- Drop-on grounding connection
- Spring clamp to accept solid and stranded wire



CSCG2.5T



CSCG4T



Terminal Width	5 mm	6 mm
Height x Length	36 x 58 mm	42 x 65 mm
Stripping Length	15 mm	13 mm
Insulation Material	Polyamide 6.6	
Type of Connection	2 spring clamp connection, grounding through alloy feet	
Approvals	* 	
Wire Range	22-14 AWG 0.2-2.5 sq.mm 22-12 AWG	22-12 AWG 0.2-4 sq.mm 22-10 AWG
Voltage Rating	800V	
Current Rating	24A	32A
Other Approvals		
Terminal Block	CSCG2.5T	CSCG4T
DIN Rail for ordering information refer to pages 90-91		
Marking Tags		
	Cat. No. Std. Pk.	Cat. No. Std. Pk.
	MT5 100	MT6 100