

# CX SERIES

## SPRING TERMINAL BLOCKS

## SIDE ENTRY FEED THROUGH TERMINAL BLOCKS

**CXS2.5**



**CXSG2.5**



### Dimensions

	<b>CXS2.5</b>	<b>CXSG2.5</b>
Width	5 mm	5 mm
Length	43 mm	43 mm
Height w/ DIN Rail	35 x 7.5 mm 35 x 15 mm	43.5 mm 51 mm

### GROUND TYPE

### Technical Data/Ratings

Approvals				
Wire Size (solid   stranded)	<b>24-12 AWG</b>	0.2-2.5 mm <sup>2</sup>	<b>24-12 AWG</b>	0.2-2.5 mm <sup>2</sup>
Voltage Rating	600 V	1000 V	600 V	1000 V
Current Rating	20A	24A	–	–
Insulation Material	Polyamide 66		Polyamide 66	

### Installation Instructions

Wire Stripping Length	10 mm	10 mm
Screwdriver	0.5x3 mm	0.5x3 mm

### Terminal Blocks

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
<b>Grey (standard)</b>	<b>CXS2.5</b>	50	<b>CXSG2.5</b>	50
Red R	CXS2.5/R	50	Yellow / Green	
Blue BU	CXS2.5/BU	50		
Black BL	CXS2.5/BL	50		
Orange O	CXS2.5/O	50		
Green G	CXS2.5/G	50		
Yellow Y	CXS2.5/Y	50		
White W	CXS2.5/W	50		

### Accessories

	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
End Plate	EPCXS2.5	50	EPCXS2.5	50
Partition Plate	–	–	–	–
DIN Rail	2511120 CA701-15/S	20 20	2511120 CA701-15/S	20 20
End Stop	CA702 CA802 CA103	50 50 50	CA702 CA802 CA103	50 50 50
Shorting Link/ Jumpers	2 pole JX2.5/2 3 pole JX2.5/3 4 pole JX2.5/4 10 pole JX2.5/10	100 50 50 10	JX2.5/2 JX2.5/3 JX2.5/4 JX2.5/10	100 50 50 10
Warning Label	WLX2.5	100	WL2.5	100
Test Plug	TX2.5	50	TX2.5	50
Marking Tag	MT5	100	MT5	100