




4 POLE

Standard Pack 3



Rated Current (I _N)	Type/ Cat. No.
0.3A	4C03UL
0.5A	4C05UL
1.0A	4C1UL
1.6A	4C1.6UL
2.0A	4C2UL
3.0A	4C3UL
4.0A	4C4UL
5.0A	4C5UL
6.0A	4C6UL
8.0A	4C8UL
10A	4C10UL
12A	4C12UL
13A	4C13UL
15A	4C15UL
16A	4C16UL
20A	4C20UL
25A	4C25UL
30A	4C30UL
32A	4C32UL
40A	4C40UL
50A	4C50UL
60A	4C60UL
63A	4C63UL

Weight (per piece)

0.3A - 32A:

0.544 - 0.572 kg

1.199 - 1.261 lb


33A - 63A:

0.568 - 0.652 kg

1.252 - 1.437 lb


C Trip Characteristic

I_N = 0.3A - 10A rated current



C Trip Characteristic

I_N = 12A - 63A rated current



Specifications

Current/ Voltage Rating	0.3 - 63A/240V AC, 0.3-32A/480Y/277V AC
Calibration Temperature	40°C (104°F)
Ambient Temperature	-25°C to +70°C (-13°F to 158°F)
Storage Temperature	-40°C to +70°C (-40°F to 158°F)
Terminal Size Acceptability	Top: 18-3 AWG; Bottom: 18-2 AWG
Terminal Torque (min/max)	2 Nm (17.7 lb.in.) / 2.5Nm (22.2 lb.in)
Electrical Life	6,000 switching cycles ON/ OFF
Mechanical Life	10,000 switching cycles ON/ OFF
Vibration Resistance	> 15g according to DIN EN 60069-2-59 during a load with I ₁ = 1.05 x I _N
Resistance to mechanical shocks	25g @ 11ms
Degree of protection acc. IEC/EN 60529	IP20
Mounting Orientation	In any plane

Short Circuit Interrupting Capacity

Pole	Type	0.3-32A	40-63A
4	AC	10kA @ 240, 480Y/277V	10kA @ 240V