







Multi-Level Fuse Blocks, 5 x 20mm + Feed Through + Ground

CYDLGF4

CYDLGF4L6-60V

CYDLGF4L110-240V



Top: Fuse Block, 5x20mm
Mid: Feed Through Terminal
Bottom: Ground
2x2 Jumper Channels

Top: Fuse Block, 5x20mm, LED
Mid: Feed Through Terminal
Bottom: Ground
2x2 Jumper Channels

Top: Fuse Block, 5x20mm, LED
Mid: Feed Through Terminal
Bottom: Ground
2x2 Jumper Channels

Dimensions & Weight

Width	6 mm	6 mm	6 mm
Length	94.5 mm	94.5 mm	94.5 mm
Height w/ DIN Rail	35 x 7.5 mm 35 x 15 mm	90.9 mm 98.4 mm	90.9 mm 98.4 mm
Weight per piece	40.8 g	35.4 g	35.4 g

Technical Data/Ratings

Approvals						
Wire Size (solid / stranded)	24-10 AWG	0.2-4 mm ²	24-10 AWG	0.2-4 mm ²	24-10 AWG	0.2-4 mm ²
Voltage Rating	300 V	1000V AC/DC	300 V	1000V AC/DC	300 V	500V AC/DC
Current Rating Fuse (Top)	10 A	10 A	10 A	10 A	10 A	10 A
Current Rating Feed Thru (Mid)	30 A	30 A	30 A	30 A	30 A	30 A
Torque	4.5 lb-in	0.5 Nm	4.5 lb-in	0.5 Nm	4.5 lb-in	0.5 Nm
Insulation Material	Polyamide 66		Polyamide 66		Polyamide 66	

Fuse Specifications

Fuse Type	5x20 / 5x25 mm	5x20 / 5x25 mm	5x20 / 5x25 mm
LED Indicator Voltage	-	6-60V AC/DC	110-240V AC/DC

Installation Instructions

Wire Stripping Length	9 mm	9 mm	9 mm
Screwdriver	Flat Head 0.6 x 3.5 mm	Flat Head 0.6 x 3.5 mm	Flat Head 0.6 x 3.5 mm

Terminal Blocks

Grey (standard)	CYDLGF4	Cat. No.	Std. Pk.	CYDLGF4L6-60L	Cat. No.	Std. Pk.	CYDLGF4L110-240V	Cat. No.	Std. Pk.
Blue BU	CYDLGF4/BU		50	CYDLGF4L6-60L/BU		50	CYDLGF4L110-240V/BU		50
Black BL	CYDLGF4/BL		50	CYDLGF4L6-60L/BL		50	CYDLGF4L110-240V/BL		50

Additional colors available.



Accessories

DIN Rail		Cat. No.	Std. Pk.	Cat. No.	Std. Pk.	Cat. No.	Std. Pk.
		2511120	20	2511120	20	2511120	20
		CA701-15/S	20	CA701-15/S	20	CA701-15/S	20
End Stop		CA702	50	CA702	50	CA702	50
		CA802	50	CA802	50	CA802	50
		CA202	50	CA202	50	CA202	50
Shorting Link/Jumpers		JX4/2	100	JX4/2	100	JX4/2	100
		JX4/3	50	JX4/3	50	JX4/3	50
		JX4/4	50	JX4/4	50	JX4/4	50
		5 pole	-	-	-	-	-
		6 pole	-	-	-	-	-
		7 pole	-	-	-	-	-
		8 pole	JX4/8	JX4/8	10	JX4/8	10
		10 pole	JX4/10	JX4/10	10	JX4/10	10
		16 pole	JX4/16	JX4/16	10	JX4/16	10
Marking Tag		MT6	1 Pk. (100 tags)	MT6	1 Pk. (100 tags)	MT6	1 Pk. (100 tags)
Warning Label		WLX4	1 Pk. (100 tags)	WLX4	1 Pk. (100 tags)	WLX4	1 Pk. (100 tags)

HIGHLIGHTS

- #### FEATURES
- Top Level fuse link for 5x20mm fuse types
 - Middle Level Feed-Through
 - Bottom Level Grounding Terminal
 - 6mm wide compact design
 - 2 internal jumper channels on each level
 - CYDLF4L version with LED for blown fuse indication
 - Blocks can be used in AC & DC applications

APPLICATIONS

- Tight Space Fuse applications
- No need for additional Feed-Through Terminal
- Control Systems with fuse applications