GREAT Product Lines from Altech



The Most Complete line of UL489, UL508 and UL1077 DIN Rail Miniature Circuit Protection Devices

Unique standard dual connection terminals.

- A Box terminal for solid conductors or flexible conductors.
- **B** Screw terminal for forked cable lug.
- **C** Screw terminal for **ring tongue** connection.
- 1 Hinged terminal cover design allows easy access to terminal screws.2 Individual Part Number is shown on each circuit breaker.
- 3 Designated marking area is protected with clear hinged cover.
- 4 DIN Clip can be released when necessary.
- 5 Flexible replaceable terminal barriers (UL489).

Liste Listed Lis

Polycarbonate Enclosed Motor Disconnect Switch

A Local Disconnect right at the motor

These enclosed switches can be used locally at the motor.
They are NEMA Type 4 and IP65 rated. Resistant against UV rays and many chemicals.

One of the most COMPACT IN THE INDUSTRY

Integrated Handle in the cover

Available in yellow/red handle or black handle 3 or 4 poles models available 16A and up to 150A models 600V AC maximum voltage NEMA Type 4X rated Small Size: 96.4 x 106 x 140.4 mm

1/4" Padlocks

Lockable with up to 3 padlocks.



Safety Cable Pull Switches

- A Rugged metal housing
- **B** Built in emergency stop and reset button
- **C** Quickfix cable connection system

(16A and 25A versions)

- **D** Cable tension monitoring with warning
- 1 For cable lengths up to 246 feet
- 2 Two inspection windows provide cable tension & contact status
- 3 Cable tension monitoring offers warning outputs if cable becomes loose
- 4 Quickfix cable system easily attaches cable and adjusts tension
- 5 Latching style with reset/emergency stop button



Contact Altech today. 908.806.9400 www.altechcorp.com



